

Reveal Cellular Pathways

INVIVO₂ 300 Hypoxia Workstation

The Ruskin range of hypoxia workstations has been designed to replicate low oxygen “in vivo” physiology providing the ideal research platform for cell biologists and cancer researchers.

Optimum Working Capacity using Minimum Bench Space

200 x 10cm plate capacity

Rapid Sample Transfer

Interlock transfers 18 x 10cm plates in 35 seconds

Direct-Hand Access into Workstation

Using convenient cuff & sleeve system (Ezee Sleeve™)

Low Gas Consumption

Designed to work with Nitrogen for economical running costs

Safe Working Environment

VOC filtration tested and validated

Accurate Oxygen Control

Oxygen stability from 0.0% (anoxia) to 20.9% (ambient) in 0.1% increments with one touch sensor calibration

Accurate CO₂ Control

CO₂ stability from 0.0% to 30.0% in 0.1% increments

Cycle Programming

Allows a user-defined timed sequence of up to 4 different O₂ and CO₂ concentrations

Accurate Temperature Control

Incubation control from Ambient + 5°C to 45°C

Accurate Humidity Control

Option of ultrasonic humidity system to give precise environmental control

innovation in incubation

Product Specifications

Workstation Fabrication

- Solvent Bonded Acrylic

Bench Space Requirements

- Height of Unit (excluding stand) 26"
- Width of Unit (including GMQ) 44"
- Depth 26"

Internal Workstation Dimensions

- Height 16"
- Width 19"
- Depth 18"
- Maximum Capacity 270 x 10cm Plates
- Working Capacity 200 x 10cm Plates

Workstation Weight

- Weight approx. 165 lbs

Interlock Dimensions

- Height 8"
- Width 6"
- Depth 9"
- Maximum Capacity 18 x 10cm Plates

Interlock Cycle Time

- 35 Seconds

Atmosphere Control

- Temperature Ambient + 5°C - 45°C
- Humidity Control Ambient - 85% RH
- O₂ Control 0.0% - 20.9%
- CO₂ Control 0.0% - 30.0%
- Activated Carbon Filtration System

Standard Accessories

Workstation

- Gas Mixer Q
- Internal Mains Socket
- Single Plate Entry System
- Direct-hand Access using Ezee Sleeve™ System
- Detox Sachet
- Energy Saving Fluorescent Lamp
- Internal Halogen Spot Lamp

Gas Control Software

- USB Communications Port
- 7 Days Continuous Storage of Event Log Data
- One Touch Calibration (O₂)
- On-Screen Fault Assistance
- Cycle Programming

Alarms

- Temperature - Visual and Audible
- Humidity - Visual
- Gas Low Pressure - Visual and Audible

Optional Accessories

- Cable Gland Port
- Vacuum Line Port
- Gas Sample Port
- Ultrasonic Humidification System
- Workstation Stand
- Catalyst Sachet
- Anaerobic Indicator Strips
- Gas Tank Regulators
- Gas Tank Filter Modules
- Power Failure Back up System
- Data Logging Connection

Gas Supply

- Up to 4 Separate Cylinders: H₂/N₂; CO₂; N₂; Air

INVIVO₂ 300

Hypoxia Workstation

The Ruskinn brand was founded in 1993 and rapidly became established as one of the world's leading suppliers and manufacturers of anaerobic and modified atmosphere workstations. Ruskinn's purpose built factory is located within the Sony Technology Centre near Pencoed in South Wales, UK. Ruskinn's range of high quality workstations is available worldwide through a global network of carefully selected distributors.



INVIVO₂ 200
Your Personal Workstation



INVIVO₂ 300
Compact Workstation
- Larger Interlock



INVIVO₂ 400
Our Most Popular Workstation



INVIVO₂ 500
Facilitates Transfer of Small Equipment



INVIVO₂ 1000
Dual Chambers - the Best Choice for Large Labs



SCI-TIVE
Total In Vitro Environment
Our Most Advanced Workstation
Imaging ready system, also features HEPA filtration



Gas Mixer Q
Standard on all INVIVO₂
Workstations
(Integrated on SCI-TIVE)

BAKER BioScience Solutions

Sold exclusively in the United States by Baker BioScience Solutions
A Division of The Baker Company, Inc.

Baker BioScience Solutions
The Baker Company, Inc.
P.O. Drawer E
161 Gatehouse Road
Sanford, Maine 04073 USA
sales@bakerbioscience.com
www.bakerbioscience.com

 **RUSKINN**
TECHNOLOGY LTD